

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 27.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *AGITAN® 230*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Defoamers, Anti-foaming agent*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MÜNZING CHEMIE GmbH
Münzingstrasse 2
74232 Abstatt, Germany
E-Mail: info@munzing.com
Tel.: +49 7131 987-100
- **Further information obtainable from:**
Product Safety Department
E-mail (MSDS): msds@munzing.com
- **1.4 Emergency telephone number:** *For Chemical Emergencies: CHEMTREC: +1 703 741 5970*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified, according to the CLP regulation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** *Void*
- **Hazard pictograms** *Void*
- **Signal word** *Void*
- **Hazard statements** *Void*
- **Additional information:**
Safety data sheet available on request.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *None.*
- **vPvB:** *None.*

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:**
hydrocarbons
hydrophobic silica
emulsifiers
mod. fatty substance

· **Dangerous components:**

<i>CAS: 64742-56-9</i> <i>EINECS: 265-159-2</i> <i>Reg.nr.: 01-2119480132-48</i>	<i>Distillates (petroleum), solvent-dewaxed light paraffinic</i> <i>Asp. Tox. 1, H304</i>	<i>75-100%</i>
<i>CAS: 64742-53-6</i> <i>EINECS: 265-156-6</i> <i>Reg.nr.: 01-2119480375-34</i>	<i>Distillates (petroleum), hydrotreated light naphthenic</i> <i>Asp. Tox. 1, H304</i>	<i>10-20%</i>

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 27.06.2016

Trade name: AGITAN® 230

(Contd. of page 1)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Protect from heat.
Keep ignition sources away - Do not smoke.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 27.06.2016

Trade name: AGITAN® 230

(Contd. of page 2)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

ACGIH-TWA	Long-term value: 5 mg/m ³ mineral oil mist
-----------	--

CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

ACGIH-TWA	Long-term value: 5 mg/m ³ oil mist
-----------	--

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

- **Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

- **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The determined penetration times according to EN 374 part III are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling

- **Body protection:** Protective work clothing

EN

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 27.06.2016

Trade name: AGITAN® 230

(Contd. of page 3)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Colour: Yellowish

· **Odour:** Mild

· **Odour threshold:** Not determined.

· **pH-value (20 g/l) at 20 °C:** ≈ 7.5 (DIN ISO 976)

· **Change in condition**

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: > 100 °C

· **Flash point:** > 100 °C (DIN EN ISO 2719)

· **Flammability (solid, gas):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: ≈ 0.6 Vol % (01-2119487077-29)

Upper: ≈ 6.5 Vol % (01-2119487077-29)

· **Oxidising properties** None.

· **Vapour pressure:** Not determined.

· **Density at 20 °C:** ≈ 0.85 g/cm³ (DIN EN ISO 2811-1)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

Dynamic at 20 °C: ≈ 1000 mPas (DIN EN ISO 3219)

Kinematic at 40 °C: > 20.5 mm²/s (DIN EN ISO 51562)

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 27.06.2016

Trade name: AGITAN® 230

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. of page 4)

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>5,000 mg/kg (rabbit)
--------	------	-----------------------

CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>5,000 mg/kg (rabbit)
--------	------	-----------------------

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

LL50	>100 mg/l (daphnia)
------	---------------------

EL50	>100 mg/l (alga)
------	------------------

	>100 mg/l (fish)
--	------------------

CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

LL50	>100 mg/l (alga)
------	------------------

	>100 mg/l (daphnia)
--	---------------------

- 12.2 Persistence and degradability No further relevant information available.
- Other information: The product is not easily biodegradable.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Behaviour in sewage processing plants:
Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not release untreated into natural waters.
- Additional ecological information:
- General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 27.06.2016

Trade name: AGITAN® 230

(Contd. of page 5)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **12.5 Results of PBT and vPvB assessment**

According to Annex XIV of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Self classification.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

07 06 08*	other still bottoms and reaction residues
-----------	---

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR/RID/ADN, ADN, IMDG, IATA** Void

· **14.2 UN proper shipping name**

· **ADR/RID/ADN, ADN, IMDG, IATA** Void

· **14.3 Transport hazard class(es)**

· **ADR/RID/ADN, ADN, IMDG, IATA**

· **Class** Void

· **14.4 Packing group**

· **ADR/RID/ADN, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

Not a dangerous good to the above specifications.

· **UN "Model Regulation":**

Void

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 27.06.2016

Trade name: AGITAN® 230

(Contd. of page 6)

- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (German AwSV, Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H304 May be fatal if swallowed and enters airways.

- **Department issuing SDS:**

Product Safety Department

E-Mail: msds@munzing.com

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Asp. Tox. 1: Aspiration hazard – Category 1

- *** Data compared to the previous version altered.**