

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 05.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *AGITAN® DF 691*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Defoamers, Anti-foaming agent*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MÜNZING CHEMIE GmbH
Münzingstrasse 2
74232 Abstatt, Germany
E-Mail: info@munzing.com
Tel.: +49 7131 987-100
- **Further information obtainable from:**
Product Safety Department
E-mail (MSDS): msds@munzing.com
- **1.4 Emergency telephone number:** *For Chemical Emergencies: CHEMTREC: +1 703 741 5970*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified, according to the CLP regulation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** *Void*
- **Hazard pictograms** *Void*
- **Signal word** *Void*
- **Hazard statements** *Void*
- **Additional information:**
Safety data sheet available on request.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *None.*
- **vPvB:** *None.*

* **SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterisation: Mixtures**
- **Description:**
hydrocarbons
non-ionic emulsifiers

· **Dangerous components:**

<i>CAS: 64742-56-9</i>	<i>Distillates (petroleum), solvent-dewaxed light paraffinic</i>	<i>75-100%</i>
<i>EINECS: 265-159-2</i>	<i>Asp. Tox. 1, H304</i>	
<i>Reg.nr.: 01-2119480132-48</i>		

- **Additional information:** *For the wording of the listed hazard phrases refer to section 16.*

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** *Immediately remove any clothing soiled by the product.*
- **After inhalation:** *Supply fresh air; consult doctor in case of complaints.*

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 05.11.2018

Trade name: AGITAN® DF 691

(Contd. of page 1)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Protect from heat.
Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 05.11.2018

Trade name: AGITAN® DF 691

· 7.3 **Specific end use(s)** No further relevant information available.

(Contd. of page 2)

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

ACGIH-TWA	Long-term value: 5 mg/m ³ mineral oil mist
-----------	----------------------------------------------------------

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The determined penetration times according to EN 374 part III are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Safety glasses

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Yellow-brown

· Odour:	Slight
-----------------	--------

· Odour threshold:	Not determined.
---------------------------	-----------------

· pH-value (20 g/l) at 20 °C:	≈ 7 (DIN ISO 976)
--------------------------------------	---------------------------

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 05.11.2018

Trade name: AGITAN® DF 691

(Contd. of page 3)

· Change in condition Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	> 250 °C
· Flash point:	> 100 °C (DIN EN ISO 2719)
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower:	≈ 0.6 Vol % (01-2119487077-29)
Upper:	≈ 6.5 Vol % (01-2119487077-29)
· Oxidising properties	None.
· Vapour pressure:	Not determined.
· Density at 20 °C:	≈ 0.87 g/cm ³ (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Dispersible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C:	≈ 1000 mPas (DIN EN ISO 3219)
Kinematic at 40 °C:	> 20.5 mm ² /s (DIN EN ISO 51562)
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Flammable vapour-air mixtures may develop if stored in large receptacles and above room temperature. Can react violently with oxygen rich (oxidising) material. Danger of Explosion.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 05.11.2018

Trade name: AGITAN® DF 691

(Contd. of page 4)

Dermal	LD50	>5,000 mg/kg (rabbit)
--------	------	-----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

LL50	>100 mg/l (daphnia)
------	---------------------

EL50	>100 mg/l (alga)
------	------------------

	>100 mg/l (fish)
--	------------------

· 12.2 Persistence and degradability

A part of the components is heavily biodegradable.

A part of the single components easily eliminable from water.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· Ecotoxicological effects:

· Behaviour in sewage processing plants:

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not release untreated into natural waters.

· Additional ecological information:

· General notes:

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

According to the criteria of the EU-classification and labelling "dangerous for environment"(93/21/EWG) the substance/ the product has to be classified as non-hazardous for the environment.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

According to Annex XIV of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Self classification.

· 12.6 Other adverse effects

No further relevant information available.

EN

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.12.2018

Version number 1

Revision: 05.11.2018

Trade name: AGITAN® DF 691

(Contd. of page 6)

· **Relevant phrases**

H304 May be fatal if swallowed and enters airways.

· **Department issuing SDS:**

Product Safety Department

E-Mail: msds@munzing.com

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

EN