

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2021

Version number 3

Revision: 11.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** AGITAN® DF 6236 M
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Defoamers, Anti-foaming agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MÜNZING CHEMIE GmbH
Münzingstrasse 2
74232 Abstatt, Germany
E-Mail: info@munzing.com
Tel.: +49 7131 987-100
- **Further information obtainable from:**
Product Safety Department
E-mail (MSDS): msds@munzing.com
- **1.4 Emergency telephone number:** For Chemical Emergencies: CHEMTREC: +1 703 741 5970

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements**
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** None.
- **vPvB:** None.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

CAS: 64742-56-9 EINECS: 265-159-2 Reg.nr.: 01-2119480132-48	Distillates (petroleum), solvent-dewaxed light paraffinic Asp. Tox. 1, H304	50-75%
CAS: 9005-00-9 NLP: 500-017-8 Reg.nr.: 01-2119977092-34	Stearyl alcohol, ethoxylated Aquatic Acute 1, H400; Aquatic Chronic 2, H411	5-<10%

- **SVHC** None.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2021

Version number 3

Revision: 11.12.2020

Trade name: **AGITAN® DF 6236 M**

(Contd. of page 1)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** None.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2021

Version number 3

Revision: 11.12.2020

Trade name: AGITAN® DF 6236 M

(Contd. of page 2)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

CAS: 9005-00-9 Stearyl alcohol, ethoxylated

Oral	consumer, long-term exposure, systemic effects	25 mg/kg bw/day (human)
Dermal	worker, long-term exposure, systemic effects	2080 mg/kg bw/day (human)
	consumer, long-term exposure, systemic effects	1250 mg/kg bw/day (human)
Inhalative	worker, long-term exposure, systemic effects	294 mg/m ³ (human)
	consumer, long-term exposure, local effects	87 mg/m ³ (human)

· **PNECs**

CAS: 9005-00-9 Stearyl alcohol, ethoxylated

fresh water	0,0019 mg/l (not specified)
marine water	0,0019 mg/l (not specified)
sediment (fresh water)	81,1 mg/kg (not specified)
sediment (marine water)	81,1 mg/kg (not specified)
sewage treatment plant	1,4 mg/l (not specified)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

· **Protection of hands:**

Oil resistant gloves

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0,5$ mm

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2021

Version number 3

Revision: 11.12.2020

Trade name: AGITAN® DF 6236 M

(Contd. of page 3)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling
- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Fluid
- **Colour:** Yellowish
- **Odour:** Mineral-oil-like
- **Odour threshold:** Not determined.

· **pH-value (20 g/l) at 20 °C:** ≈ 7 (DIN ISO 976)

· **Change in condition**

- **Melting point/freezing point:** Undetermined.
- **Initial boiling point and boiling range:** > 180 °C

· **Flash point:** > 180 °C (DIN EN ISO 2719)

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· **Explosion limits:**

- **Lower:** ≈ 1 Vol % (01-2119480132-48)
- **Upper:** ≈ 10 Vol % (01-2119480132-48)

· **Oxidising properties:** None.

· **Vapour pressure:** Not determined.

· **Density at 20 °C:** ≈ 0,89 g/cm³ (DIN EN ISO 2811-1)

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with water:**

Fully miscible.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

- **Dynamic at 20 °C:** ≈ 700 mPas (DIN EN ISO 3219)
- **Kinematic at 40 °C:** > 20,5 mm²/s (DIN EN ISO 51562)

· **Solvent separation test:** Not determined

· **9.2 Other information:** No further relevant information available.

EU

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2021

Version number 3

Revision: 11.12.2020

Trade name: AGITAN® DF 6236 M

(Contd. of page 4)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Flammable vapour-air mixtures may develop if stored in large receptacles and above room temperature.
Can react violently with oxygen rich (oxidising) material. Danger of Explosion.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >5000 mg/kg (rabbit)

CAS: 9005-00-9 Stearyl alcohol, ethoxylated

Oral LD50 >21000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

LL50 >100 mg/l (daphnia)

EL50 >100 mg/l (alga)

>100 mg/l (fish)

CAS: 9005-00-9 Stearyl alcohol, ethoxylated

LC50 5,6 mg/l (fish) (*Oncorhynchus mykiss* / 96 h)

- **12.2 Persistence and degradability** A part of the components is heavily biodegradable.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2021

Version number 3

Revision: 11.12.2020

Trade name: AGITAN® DF 6236 M

(Contd. of page 5)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Behaviour in sewage processing plants:**
Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not release untreated into natural waters.
- **Additional ecological information:**
- **General notes:**
Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.
According to the criteria of the EU-classification and labelling "dangerous for environment"(93/21/EWG) the substance/ the product has to be classified as non-hazardous for the environment.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
According to Annex XIV of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Self classification.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - **European waste catalogue**
- | | |
|----------|---|
| 16 03 06 | organic wastes other than those mentioned in 16 03 05 |
|----------|---|
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.
 - **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | | |
|--|---------------------------------------|------|
| · 14.1 UN-Number | · ADR/RID/ADN, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | · ADR/RID/ADN, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | · ADR/RID/ADN, ADN, IMDG, IATA | Void |
| · Class | | Void |
| · 14.4 Packing group | · ADR/RID/ADN, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | | |
| · Marine pollutant: | | No |

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.01.2021

Version number 3

Revision: 11.12.2020

Trade name: AGITAN® DF 6236 M

(Contd. of page 6)

- | | |
|--|---|
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | Not a dangerous good to the above specifications. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **National regulations:**

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H304 May be fatal if swallowed and enters airways.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

- **Department issuing SDS:**

Product Safety Department

E-Mail: msds@munzing.com

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3