

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2018

Version number 2

Revision: 28.09.2018

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** *AGITAN® 260*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the mixture** *Defoamers, Anti-foaming agent*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*MÜNZING CHEMIE GmbH*  
*Münzingstrasse 2*  
*74232 Abstatt, Germany*  
*E-Mail: info@munzing.com*  
*Tel.: +49 7131 987-100*
- **Further information obtainable from:**  
*Product Safety Department*  
*E-mail (MSDS): msds@munzing.com*
- **1.4 Emergency telephone number:** *+49 761 19240 (Vergiftungs-Informations-Zentrale VIZ Freiburg)*

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
*The product is not classified, according to the CLP regulation.*
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** *Void*
- **Hazard pictograms** *Void*
- **Signal word** *Void*
- **Hazard statements** *Void*
- **Additional information:**  
*Safety data sheet available on request.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *None.*
- **vPvB:** *None.*

**SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterisation: Mixtures**
- **Description:**  
*hydrocarbons*  
*hydrophobic silica*  
*emulsifiers*  
*mod. fatty substance*

· **Dangerous components:**

<i>CAS: 64742-55-8</i> <i>EINECS: 265-158-7</i> <i>Reg.nr.: 01-2119487077-29</i>	<i>Distillates (petroleum), hydrotreated light paraffinic</i> <i>Asp. Tox. 1, H304</i>	<i>75-100%</i>
<i>CAS: 8042-47-5</i> <i>EINECS: 232-455-8</i> <i>Reg.nr.: 01-2119487078-27</i>	<i>White mineral oil (petroleum)</i> <i>Asp. Tox. 1, H304</i>	<i>5-&lt;10%</i>

- **SVHC** *None.*

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2018

Version number 2

Revision: 28.09.2018

Trade name: AGITAN® 260

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 1)

#### **SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective clothing.  
Use respiratory protective device against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Protect from heat.  
Keep ignition sources away - Do not smoke.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2018

Version number 2

Revision: 28.09.2018

**Trade name: AGITAN® 260**

(Contd. of page 2)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**CAS: 64742-55-8 Distillates (petroleum), hydrotreated light paraffinic**

ACGIH - TWA	Long-term value: 5 mg/m <sup>3</sup> mineral oil mist
-------------	--

**CAS: 8042-47-5 White mineral oil (petroleum)**

ACGIH-TWA	Long-term value: 5 mg/m <sup>3</sup> oil mist
-----------	--

· **DNELs**

**CAS: 8042-47-5 White mineral oil (petroleum)**

Oral	consumer, long-term exposure, systemic effects	40 mg/kg bw/day (human)
Dermal	worker, long-term exposure, systemic effects	220 mg/kg bw/day (human)
	consumer, long-term exposure, systemic effects	92 mg/kg bw/day (human)
Inhalative	worker, long-term exposure, systemic effects	160 mg/m <sup>3</sup> (human)
	consumer, long-term exposure, systemic effects	35 mg/m <sup>3</sup> (human)

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Avoid contact with the eyes and skin.

- **Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2018

Version number 2

Revision: 28.09.2018

**Trade name: AGITAN® 260**

(Contd. of page 3)

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling
- **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Fluid  
 · **Colour:** Yellowish  
 · **Odour:** Mild

· **Odour threshold:** Not determined.

· **pH-value (20 g/l) at 20 °C:** ≈ 7.5 (DIN ISO 976)

· **Change in condition**

· **Melting point/freezing point:** Undetermined.  
 · **Initial boiling point and boiling range:** > 180 °C

· **Flash point:** > 100 °C (DIN EN ISO 2719)

· **Flammability (solid, gas):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· **Lower:** ≈ 1 Vol % (01-0000020163-82)  
 · **Upper:** ≈ 10 Vol % (01-0000020163-82)

· **Oxidising properties:** None.

· **Vapour pressure:** Not determined.

· **Density at 20 °C:** ≈ 0.83 g/cm<sup>3</sup> (DIN EN ISO 2811-1)

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with water:**

Insoluble.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· **Dynamic at 20 °C:** ≈ 700 mPas (DIN EN ISO 3219)  
 · **Kinematic at 40 °C:** > 20.5 mm<sup>2</sup>/s (DIN EN ISO 51562)

· **9.2 Other information:** No further relevant information available.

EN

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2018

Version number 2

Revision: 28.09.2018

Trade name: AGITAN® 260

(Contd. of page 4)

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**CAS: 64742-55-8 Distillates (petroleum), hydrotreated light paraffinic**

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>5,000 mg/kg (rabbit)
--------	------	-----------------------

**CAS: 8042-47-5 White mineral oil (petroleum)**

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/kg (rabbit)
--------	------	-----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 64742-55-8 Distillates (petroleum), hydrotreated light paraffinic**

EC50	>1,000 mg/l (daphnia) (48h)
------	-----------------------------

LC50	>1,000 mg/l (fish) (96h)
------	--------------------------

IC50	>1,000 mg/l (alga) (72h)
------	--------------------------

**CAS: 8042-47-5 White mineral oil (petroleum)**

LC50	>1,000 mg/l (fish) (Leuciscus idus / 96 h (OECD 203))
------	---

LL50	>100 mg/l (daphnia) (Daphnia magna / 48 h (OECD 202))
------	---

NOELR	>100 mg/l (alga) (Pseudokirchnerella subcapitata / 72 h (OECD 201))
-------	---

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2018

Version number 2

Revision: 28.09.2018

**Trade name: AGITAN® 260**

(Contd. of page 5)

- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**  
According to Annex XIV of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Self classification.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

07 06 08*	other still bottoms and reaction residues
-----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

- |  |   |
|--|---|
| · <b>14.1 UN-Number</b>  |   |
| · <b>ADR/RID/ADN, ADN, IMDG, IATA</b>  | Void  |
| · <b>14.2 UN proper shipping name</b>  |   |
| · <b>ADR/RID/ADN, ADN, IMDG, IATA</b>  | Void  |
| · <b>14.3 Transport hazard class(es)</b>   |   |
| · <b>ADR/RID/ADN, ADN, IMDG, IATA</b>  |   |
| · <b>Class</b>   | Void  |
| · <b>14.4 Packing group</b>  |   |
| · <b>ADR/RID/ADN, IMDG, IATA</b>   | Void  |
| · <b>14.5 Environmental hazards:</b>   |   |
| · <b>Marine pollutant:</b>   | No  |
| · <b>14.6 Special precautions for user</b>                                       | Not applicable.                                   |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable.                                   |
| · <b>Transport/Additional information:</b>                                       | Not a dangerous good to the above specifications. |
| · <b>UN "Model Regulation":</b>  | Void  |

EN

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2018

Version number 2

Revision: 28.09.2018

**Trade name: AGITAN® 260**

(Contd. of page 6)

### **SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (German AwSV, Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**  
*H304 May be fatal if swallowed and enters airways.*
- **Department issuing SDS:**  
*Product Safety Department*  
*E-Mail: [msds@munzing.com](mailto:msds@munzing.com)*
- **Abbreviations and acronyms:**  
*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*  
*IMDG: International Maritime Code for Dangerous Goods*  
*IATA: International Air Transport Association*  
*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*  
*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*DNEL: Derived No-Effect Level (REACH)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*SVHC: Substances of Very High Concern*  
*vPvB: very Persistent and very Bioaccumulative*  
*Asp. Tox. 1: Aspiration hazard – Category 1*
- **\* Data compared to the previous version altered.**