

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** *AGITAN® 703 N*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the mixture** *Defoamers, Anti-foaming agent*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*MÜNZING CHEMIE GmbH*  
*Münzingstrasse 2*  
*74232 Abstatt*  
*GERMANY*  
*E-Mail: info@munzing.com*  
*Tel.: +49 7131 987-100*
- **Further information obtainable from:**  
*Product Safety Department*  
*E-mail (MSDS): msds@munzing.com*
- **1.4 Emergency telephone number:** *+49 761 19240 (Vergiftungs-Informations-Zentrale VIZ Freiburg)*

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
*Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.*
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
*The product is classified and labelled according to the CLP regulation.*
- **Hazard pictograms**



GHS09

- **Signal word** *Void*
- **Hazard statements**  
*H411 Toxic to aquatic life with long lasting effects.*
- **Precautionary statements**  
*P273 Avoid release to the environment.*  
*P391 Collect spillage.*  
*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *None.*
- **vPvB:** *None.*

EN

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

Trade name: AGITAN® 703 N

(Contd. of page 1)

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Description:**

hydrocarbons  
hydrophobic silica acid  
emulsifiers

· **Dangerous components:**

CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27	White mineral oil (petroleum) ----- Asp. Tox. 1, H304	50-75%
CAS: 27458-92-0 EINECS: 248-469-2 Reg.nr.: 01-2119488528-21	Isotridecan-1-ol ----- Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	5-<10%

· **SVHC** None.

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

· **5.3 Advice for firefighters**

· **Protective equipment:** Do not inhale explosion gases or combustion gases.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective clothing.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

**Trade name: AGITAN® 703 N**

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Protect from heat.  
Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**CAS: 8042-47-5 White mineral oil (petroleum)**

ACGIH-TWA	Long-term value: 5 mg/m <sup>3</sup> oil mist
-----------	--

· **DNELs**

**CAS: 8042-47-5 White mineral oil (petroleum)**

Oral	consumer, long-term exposure, systemic effects	40 mg/kg bw/day (human)
Dermal	worker, long-term exposure, systemic effects	220 mg/kg bw/day (human)
	consumer, long-term exposure, systemic effects	92 mg/kg bw/day (human)
Inhalative	worker, long-term exposure, systemic effects	160 mg/m <sup>3</sup> (human)
	consumer, long-term exposure, systemic effects	35 mg/m <sup>3</sup> (human)

**CAS: 27458-92-0 Isotridecan-1-ol**

Oral	consumer, long-term exposure, systemic effects	2.1 mg/kg bw/day (human)
Dermal	worker, long-term exposure, systemic effects	6.94 mg/kg bw/day (human)
	consumer, long-term exposure, systemic effects	4.2 mg/kg bw/day (human)
Inhalative	worker, long-term exposure, systemic effects	24.5 mg/m <sup>3</sup> (human)
	consumer, long-term exposure, systemic effects	7.3 mg/m <sup>3</sup> (human)

· **PNECs**

**CAS: 27458-92-0 Isotridecan-1-ol**

fresh water	0.000072 mg/l (not specified)
-------------	-------------------------------

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

**Trade name: AGITAN® 703 N**

(Contd. of page 3)

marine water	0.000007 mg/l (not specified)
aqua - intermittent release	0.003 mg/l (not specified)
soil	0.314 mg/kg (not specified)
sediment (fresh water)	0.021 mg/kg (not specified)
sediment (marine water)	0.002 mg/kg (not specified)
sewage treatment plant	10 mg/l (not specified)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Avoid contact with the eyes and skin.

· **Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The determined penetration times according to EN 374 part III are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

· **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Fluid

· **Colour:** Yellowish

· **Odour:** Mild

· **Odour threshold:** Not determined.

· **pH-value (20 g/l) at 20°C:**  $\approx 8$  (DIN ISO 976)

· **Change in condition**

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:**  $> 100^\circ\text{C}$

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

Trade name: AGITAN® 703 N

(Contd. of page 4)

· <b>Flash point:</b>	> 100°C (DIN EN ISO 2719)
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Ignition temperature:</b>	
<b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	≈ 1 Vol % (01-2119487078-27)
<b>Upper:</b>	≈ 10 Vol % (01-2119487078-27)
· <b>Oxidising properties</b>	None.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density at 20°C:</b>	≈ 0,92 g/cm <sup>3</sup> (DIN EN ISO 2811-1)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Emulsifiable.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20°C:</b>	≈ 250 mPas (DIN EN ISO 3219)
<b>Kinematic at 40°C:</b>	> 20,5mm <sup>2</sup> /s (DIN EN ISO 51562)
· <b>Solvent content:</b>	
<b>VOC (EC)</b>	0.00 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**CAS: 8042-47-5 White mineral oil (petroleum)**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

**Trade name: AGITAN® 703 N**

(Contd. of page 5)

**CAS: 27458-92-0 Isotridecan-1-ol**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	6,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 8042-47-5 White mineral oil (petroleum)**

LC50	>1,000 mg/l (fish) ( <i>Leuciscus idus</i> / 96 h (OECD 203))
LL50	>100 mg/l (daphnia) ( <i>Daphnia magna</i> / 48 h (OECD 202))
NOELR	>100 mg/l (alga) ( <i>Pseudokirchnerella subcapitata</i> / 72 h (OECD 201))

**CAS: 27458-92-0 Isotridecan-1-ol**

EC50 (static)	0.297 mg/l (alga) ( <i>Desmodesmus subspicatus</i> / 72 h (OECD 201))
	0.391 mg/l (daphnia) ( <i>Daphnia magna</i> / 48 h (OECD 202))
LC50	0.55 mg/l (fish) ( <i>Brachydanio rerio</i> / 96 h (OECD 203))
NOEC	0.0016-0.014 mg/l (daphnia) ( <i>Daphnia magna</i> / 21 d (OECD 211))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Behaviour in sewage processing plants:**  
Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not release untreated into natural waters.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**  
According to Annex XIV of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Self classification.
- **12.6 Other adverse effects** No further relevant information available.

EN

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

Trade name: AGITAN® 703 N

(Contd. of page 6)

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

07 06 08\* | other still bottoms and reaction residues

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

· **14.1 UN-Number**

· **ADR/RID/ADN, IMDG, IATA** UN3082

· **14.2 UN proper shipping name**

· **ADR/RID/ADN** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isotridecan-1-ol)  
· **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isotridecan-1-ol), MARINE POLLUTANT  
· **IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isotridecan-1-ol)


· **14.3 Transport hazard class(es)**

· **ADR/RID/ADN, IATA**



· **Class** 9 Miscellaneous dangerous substances and articles.  
· **Label** 9

· **IMDG**



· **Class** 9 Miscellaneous dangerous substances and articles.

· **14.4 Packing group**

· **ADR/RID/ADN, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** Yes  
Symbol (fish and tree)  
· **Special marking (ADR/RID/ADN):** Symbol (fish and tree)  
· **Special marking (IATA):** Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.  
· **Danger code (Kemler):** 90  
· **EMS Number:** F-A,S-F

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

Trade name: AGITAN® 703 N

(Contd. of page 7)

· <b>Stowage Category</b>	A
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
· <b>ADR/RID/ADN</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	E
· <b>UN "Model Regulation":</b>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOTRIDECAN-1-OL), 9, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.
- **Department issuing SDS:**  
Product Safety Department  
E-Mail: [msds@munzing.com](mailto:msds@munzing.com)
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern

(Contd. on page 9)



***Safety data sheet***  
**according to 1907/2006/EC, Article 31**

Printing date 19.10.2017

Version number 1

Revision: 18.03.2016

**Trade name: AGITAN® 703 N**

(Contd. of page 8)

*vPvB: very Persistent and very Bioaccumulative*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*

*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

EN