

# AGITAN<sup>®</sup> A210

## TECHNICAL INFORMATION

### Defoamer for aqueous systems

<b>Composition:</b>	Blend of mineral oil and non-ionic surfactants, APEO free		
<b>Appearance:</b>	liquid		
<b>Colour:</b>	yellowish turbid		
<b>Typical Properties:</b>	<b>Active ingredients:</b>	approx. 95.0 %	
	<b>Consistency:</b>	approx. 600 - 1,200 mPas/cps	

*This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.*

**Properties/applications:** AGITAN A209 is a defoamer for all common emulsion systems. It provides the following properties: controls foaming and aeration during paint manufacture, filling and application; good compatibility in a wide range of systems; retains high and long lasting efficiency; effective over a wide pH range.

**Main applications:**  
- Architectural coatings and plasters  
- Adhesives  
- Polymeric dispersions  
- UV printing inks

**Recommended levels/use:** AGITAN A 210 should be agitated before use and used without dilution

**Storage/handling:** Always mix prior to use as the product tends to separate slightly  
Mix product and retest for quality after one year from the date of manufacture.  
The minimum shelf life in closed containers is 12 months from the date of manufacture.  
Refer to Material Safety Data Sheet for additional handling information.

**Packaging:** Drums holding 276 lbs/ 125 kg net or 5 gallon pail holding 44 lbs/ 20 kg net.