

AGITAN[®] DF 6575 GM

TECHNICAL INFORMATION

Defoamer for aqueous systems

Composition: Mixture of mineral oil and non ionic surfactants, APEO free

Appearance: liquid
Colour: yellowish, turbid

Typical Properties:

Active ingredients:	approx. 96 %
Viscosity:	approx. 1400 mPa s
Density at 20°C:	approx. 0.89 g/cm ³
Flash point:	> 170°C
Solubility in water:	insoluble
pH (2% in dist. water):	approx. 7

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: AGITAN DF 6575 GM is a defoamer for all common emulsion systems. It provides the following properties:

- Extremely versatile
- Good compatibility
- Effective over a wide pH range

Main applications:

- Adhesives
- Emulsion paints

Recommended levels/use: AGITAN DF 6575 GM should be agitated before use and used without dilution. Suggested dosage for some typical applications:

Adhesives:	
- Starch, Dextrine, Casein	0.1-0.2 %
- Acrylic, PV Acetate, PV Alcohol	0.1-0.3 %
Water-based paints:	
- Decorative	0.1-0.3 %
- Coatings for public works, structural engineering, A.C.E.	0.1-0.2 %
- Wood coatings	0.1-0.3 %

Storage/handling: AGITAN DF 6575 GM is sensitive to freezing and should be stored between 5 and 35 °C. As the product tends to separate it should be mixed before use. The minimum shelf life in closed containers is 15 months from the date of manufacture.

Packaging: Totes holding 900 kg net, drums holding 130 kg net or cans holding 25 kg net.