

AGITAN[®] P 833

TECHNICAL INFORMATION

Powder defoamer

| | | |
|----------------------------|--|---|
| Composition: | Blend of liquid hydrocarbons and polyglycols on an inorganic carrier | |
| Appearance: | powder | |
| Colour: | white | |
| Typical Properties: | Ash: | approx. 42 % |
| | Consistency: | powder |
| | Apparent density: | approx. 390 g/l |
| | Solubility in water: | hydrophobic product, dispersible in water |

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: AGITAN P 833 is recommended for application in dry blends which are dissolved in water before application. The addition of AGITAN P 833 results in low foaming solutions, specifically aqueous pastes or masses with very low air content. In some mortar systems AGITAN P 833 shows a plastisizing effect, meaning the spreading value is increased. This is ideal for jointless flooring compounds.

Main applications:

- Joint fillers and putties
- Leveling compounds
- Screeds (cement and anhydride based)
- Gypsum
- Cement
- Mortars
- Powder paints
- Adhesives

Recommended levels/use: Ladder studies are recommended to determine optimum concentration level. Normal dosage ranges from 0.1 to 1 % on finished product. Handling of AGITAN P 833 is convenient with respect to flowability, dusting and ease of incorporation.

Storage/handling: AGITAN P 833 is not sensitive to freezing. For better handling it should be stored dry between 15 and 25 °C. The minimum shelf life in closed containers is 15 months from the date of manufacture.

Packaging: Pallet with 30 bags, each 15 kg (450 kg)