

AGITAN[®] P 883

TECHNICAL INFORMATION

Powder Defoamer

Composition:	Blend of natural oils and polyoxyalkylene technology	
Appearance:	powder	
Colour:	white	
Typical Properties:	Active ingredients:	approx. 99.0 %
	Ash:	approx. 42.0%
	Emulsifiable:	Moderate

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: AGITAN P 883 is an excellent universal powder defoamer specifically designed for use in construction materials. It is especially effective in thin sets and self-leveling formulations.

Main applications:
- Joint fillers and putties
- Leveling compounds
- Gypsum
- Concrete
- Mortars
- Powder paints
- Adhesives

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level from 0.1% to 1.0%, based on the weight of the formulation, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. For better handling, store at between 15°C(59°F) and 25°C(77°F). Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: Bags holding 55 lbs/ 25 kg net

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

EN

Revision: 06/14: