

# DEE FO<sup>®</sup> 718

## TECHNICAL INFORMATION

### Defoamer for aqueous systems

<b>Appearance:</b>	liquid
<b>Colour:</b>	transparent gold-tinted
<b>Typical Properties:</b>	Active ingredients: approx. 50.0%
	Consistency: approx. 200 mPas/cps

*This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.*

**Properties/applications:** DEE FO 718 is a unique, innovative solution whose performance and compatibility characteristics offer excellent efficiency, persistence, and ease of incorporation.

Main applications:  
- Printing press applications  
- Flexographic news inks

**Recommended levels/use:** The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level from 0.1% to 0.5%, based on the weight of the formulation, is recommended.

**Storage/handling:** Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

**Packaging:** Drums holding 500 lbs/ 227 kg net or 5 gallon pail holding 45 lbs/ 20 kg net.