

# FOAMTROL 10L

## TECHNICAL INFORMATION

### Defoamer for aqueous systems

<b>Composition:</b>	Blend of silicone and water	
<b>Appearance:</b>	liquid	
<b>Colour:</b>	off-white opaque	
<b>Typical Properties:</b>	Active ingredients:	approx. 10.0 %
	Consistency/Viscosity:	approx. 800 - 1,500 mPas /cps
	Density at 20°C:	approx. 8.29 lbs/gal
	Emulsifiable:	Moderate

*This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.*

**Properties/applications:** FOAMTROL 10L is a versatile, low viscosity and stable silicone emulsion effective in floor care products, wood coatings, lens polishes and in tank-side, non-FDA applications.

**Main applications:**

- Wood coatings and preservatives
- Flooring coatings
- Lens polish slurry
- Wastewater treatment
- Non-FDA tank-side

**Recommended levels/use:** The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level of 0.02% to 0.20%, based on the weight of the formulation, is recommended.

**Storage/handling:** Always mix prior to use as the product tends to separate slightly  
Store at room temperature and protect from freezing.  
Mix product and retest for quality after one year from the date of manufacture.  
The minimum shelf life in closed containers is 12 months from the date of manufacture.  
Refer to Material Safety Data Sheet for additional handling information.

**Packaging:** Totes holding 2,500 lbs/1,134 kg net, Drums holding 450 lbs/ 204 kg net and 5 gallon pail holding 40 lbs/ 18 kg net.