

# FOAM BAN<sup>®</sup> 130B

## TECHNICAL INFORMATION

### Defoamer for industrial fluids

<b>Composition:</b>	Blend of silicone compound and synthetic hydrocarbon	
<b>Appearance:</b>	liquid	
<b>Colour:</b>	clear colorless	
<b>Typical Properties:</b>	<b>Consistency:</b>	approx. 15 mPas / cps
	<b>Density:</b>	approx. 6.80 lbs/gal

*This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.*

**Properties/applications:** Foam Ban 130B is a defoamer formulated with synthetic hydrocarbons for use in non-aqueous industrial lubricants. Primary applications include hydraulic oils and gear oils.

**Main applications:**

- Lubes/Hydraulics – non-aqueous mineral oil and synthetic

**Recommended levels/use:** The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level from 0.05% to 0.10%, based on the weight of the formulation, is recommended.

**Storage/handling:** Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

**Packaging:** **U.S.** - Drums holding 380 lbs/172 kg net or 5 gallon pail holding 35 lbs/16 kg net.  
**EU** – Drums holding 264 lbs/120 kg net or 5 gallon pail holding 33 lbs/15 kg net