

FOAM BAN[®] 149

TECHNICAL INFORMATION

Defoamer for industrial fluids

Composition:	Blend of silicone compound and synthetic hydrocarbon	
Appearance:	liquid	
Colour:	clear colorless	
Typical Properties:	Consistency:	approx. 24 mPas / cps
	Density:	approx. 6.80 lbs/gal

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: Foam Ban 149 is a defoamer formulated with silicone compounds dispersed in synthetic hydrocarbons for use in non-aqueous industrial lubricants. Primary applications include hydraulic oils and gear oils.

Main applications:
- Lubes/Hydraulics – non-aqueous mineral oil and synthetic

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level from 0.05% to 0.10%, based on the weight of the formulation, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: **U.S.** - Drums holding 370 lbs/168 kg net or 5 gallon pail holding 33 lbs/15 kg net.
EU – Drums holding 264 lbs/120 kg net or 5 gallon pail holding 33 lbs/15 kg net