

FOAM BAN[®] 169

TECHNICAL INFORMATION

Defoamer for non-aqueous systems

Composition:	Blend of 3-D siloxane and synthetic hydrocarbon	
Appearance:	liquid	
Colour:	translucent	
Typical Properties:	Consistency/Viscosity:	approx. 200 mPas / cps
	Density:	approx. 7.0 lbs/gal

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: Foam Ban 169 is a defoamer formulated with siloxane compounds dispersed in synthetic hydrocarbons for use in non-aqueous industrial lubricants. It provides excellent surface foam reduction.

Main applications:

- Lubricants – mineral oil
- Lubricants – synthetic
- Hydraulic – non-aqueous

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level from 0.2% to 0.5%, based on the weight of the formulation, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. For best results, store between 10°C (50°F) to 40°C (104°F). Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: Drums holding 400 lbs/ 181 kg net or 5 gallon pail holding 35 lbs/ 16 kg net.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

EN

Revision: 03/18: