

FOAM BAN[®] 260D

TECHNICAL INFORMATION

Defoamer for aqueous industrial fluids

Composition:	Blend of 3-Dimensional siloxane and water	
Appearance:	liquid	
Colour:	off-white	
Typical Properties:	Consistency:	approx. 700 mPas / cps
	Density:	approx. 8.34 lbs/gal

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: Foam Ban 260D is a 3-dimensional siloxane compound defoamer emulsified in water for optimum efficiency and dispersibility in aqueous industrial fluids. It is mainly designed as an optimum tank-side defoamer that provides both initial foam knockdown, as well as long-term defoaming persistence.

Main applications:

- Industrial cleaners
- Metalworking fluids
- Waste water systems

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level of 100 ppm, added as needed tank-side, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. Protect from freezing. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: Drums holding 460 lbs/ 209 kg net or 5 gallon pail holding 42 lbs/ 19 kg net.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

EN

Revision: 06/14: