

# FOAM BAN<sup>®</sup> CL-125E

## TECHNICAL INFORMATION

### Universal Defoamer

<b>Composition:</b>	Blend of 3-dimensional siloxane	
<b>Appearance:</b>	liquid	
<b>Colour:</b>	opaque white	
<b>Typical Properties:</b>	<b>Active Ingredients:</b>	approx. 62.5%
	<b>Consistency/Viscosity:</b>	approx. 5,000 mPas / cps

*This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.*

**Properties/applications:** FOAM BAN CL-125E is a universal foam control agent intended for use in a broad range of cleaners, including both acidic and alkaline types. It contains 3-D siloxane technology optimized to provide better in-concentrate compatibility as well as superior defoaming efficiency for cleaner systems. This defoamer offers formulators the newest organo-modified siloxane technology available combined with the perfect balance of defoaming efficiency, stability, compatibility and value. When properly used at prescribed levels, it will not impair subsequent finishing operations, such as painting or plating.

**Recommended levels/use:** The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level between 0.1% to 0.3%, based on the weight of the formulation, is recommended.

**Storage/handling:** Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

**Packaging:** Drums holding 490 lbs/ 222 kg net or 5 gallon pail holding 42 lbs/ 19 kg net.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

EN

Revision: 06/14: