

FOAM BAN[®] HP750

TECHNICAL INFORMATION

Defoamer for industrial fluids

Composition:	Blend of 3-Dimensional Siloxane and water	
Appearance:	liquid	
Colour:	opaque off-white	
Typical Properties:	Active ingredients:	approx. 40.0 %
	Consistency/Viscosity:	approx. 58 mPas / cps
	Specific Gravity (25° C)	approx. 0.98 – 1.03
	Emulsifiable:	High
Washable:	FOAM BAN HP750 is washable under typical industrial cleaning and rinsing practices and consequently subsequent painting after washing in without defect	

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: A high efficiency, 3-Dimension Siloxane defoamer emulsion specifically designed for use in aqueous metalworking lubricants. Primary applications include soluble oils, semi-synthetic fluids, industrial cleaners, and HWC hydraulic fluids.

Main applications:

- Soluble oil petroleum based metalworking fluids
- Soluble oil vegetable based metalworking fluids
- HWC hydraulic fluids

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level from 0.10% to 0.30%, based on the weight of the formulation, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. For better handling, store at room temperature and protect from freezing. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: Drums holding 460 lbs/ 209 kg net or 5 gallon pail holding 42 lbs/ 19 kg net.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

EN

Revision: 09/17: