

FOAM BAN[®] MS-575

TECHNICAL INFORMATION

Defoamer for aqueous systems

Composition:	Blend of 3-Dimensional Siloxane and water	
Appearance:	liquid	
Colour:	translucent off-white	
Typical Properties:	Active ingredients:	approx. 73.0%
	Consistency/Viscosity:	approx. 3,000 mPas /cps
	Density at 20°C:	approx. 8.75 lbs/gal
	Emulsifiable:	Moderate
	pH (2% in dist. water):	approx. 7.6
	Washable:	FOAM BAN MS-575 is washable under typical industrial cleaning and rinsing practices and consequently subsequent painting after washing in without defect

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: FOAM BAN MS-575 is a 3-Dimensional Siloxane compound defoamer emulsion for use in aqueous metalworking fluids. Primary applications include petroleum based soluble oils, semi-synthetics and synthetic fluids.

Main applications:

- Soluble oil petroleum based metalworking fluids
- Semi-synthetic high mineral oil content metalworking fluids
- Semi-synthetic – ester/vegetable oil metalworking fluids
- Solution synthetic metalworking fluids

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level from 0.1% to 0.5%, based on the weight of the formulation, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: **US** - Drums holding 489 lbs/222 kg net or pails holding 42 lbs/19 kg net
EU - Drums holding 441 lbs/200 kg net or pails holding 55 lbs/25 kg net