

FOAM BAN[®] SB-1

TECHNICAL INFORMATION

Defoamer for industrial fluids

Composition:	Blend of special wax and mineral oil	
Appearance:	liquid	
Colour:	opaque milky	
Typical Properties:	Consistency/Viscosity:	approx. 3,500 mPas /cps

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: FOAM BAN SB-1 is an oil-based defoamer designed primarily for tank-side use in a wide variety of aqueous metalworking lubricants. It is also formulated to provide excellent compatibility, as well as long-term defoaming persistence.

Main applications:

- MW Tank-side high agitation/pressure metalworking fluids
- MW Tank-side low agitation/pressure metalworking fluids
- Paint spray booth systems

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level between 0.1% to 1.0%, based on the weight of the formulation, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. Protect from freezing. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: Drums holding 360 lbs/ 163 kg net or 5 gallon pail holding 32 lbs/ 14 kg net.