

FOAM BAN[®] SB-73

TECHNICAL INFORMATION

Defoamer for industrial fluids

Composition:	Blend of metallic stearate and mineral oil	
Appearance:	liquid	
Colour:	hazy amber	
Typical Properties:	Active ingredients:	approx. 96.5 %
	Consistency/Viscosity:	approx. 1,000 mPas /cps
	Density at 20°C:	approx. 7.28 lbs/gal
	Emulsifiable:	High

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: FOAM BAN SB-73 is an oil-based defoamer designed primarily for tank-side use in a wide variety of aqueous metalworking lubricants. It is also formulated to provide excellent compatibility, as well as long-term defoaming persistence.

Main applications:

- MW Tank-side high agitation/pressure metalworking fluids
- MW Tank-side low agitation/pressure metalworking fluids

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level of 0.1 to 1.0%, based on the weight of the formulation, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: **US** - Drums holding 399 lbs/181 kg net or pails holding 38 lbs/17 kg net
EU - Drums holding 276 lbs/125 kg net or pails holding 55 lbs/25 kg net