

FOAM BAN[®] SB-81

TECHNICAL INFORMATION

Defoamer for industrial fluids

Composition:	Blend of hydrophobic silica and mineral oil	
Appearance:	liquid	
Colour:	yellow brown turbid	
Typical Properties:	Active Ingredients:	approx. 100.0%
	Consistency/Viscosity:	approx. 500 - 1,500 mPas /cps

Emulsifiable: Highly emulsifiable

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications:	Main applications: <ul style="list-style-type: none">- Industrial, architectural and wood coatings- Printing inks – pigment grinding and letdown- Adhesives- Cleaners, especially applications under alkaline condition- Metalworking fluids and lubricants
---------------------------------	--

Recommended levels/use:	The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level between 0.1% and 1.0%, based on the weight of the formulation, is recommended.
--------------------------------	--

Storage/handling:	Always mix prior to use as the product tends to separate slightly Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.
--------------------------	--

Packaging:	Drums holding 400 lbs/ 181 kg net or 5 gallon pail holding 42 lbs/ 19 kg net.
-------------------	---