

FOAM BAN[®] SB-8

TECHNICAL INFORMATION

Defoamer for industrial fluids

Composition:	Blend of metallic stearate and mineral oil	
Appearance:	liquid	
Colour:	opaque off-white	
Typical Properties:	Consistency/Viscosity:	approx. 3,200 mPas /cps
	Density at 20°C:	approx. 6.90 lbs/gal

This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.

Properties/applications: FOAM BAN SB-8 is specifically designed to rupture and dissipate tank-side foam in the metalworking industry. The defoamer provides both initial foam knockdown, as well as long-term defoaming persistence. It is non-silicone and water miscible.

Main applications:
- MW Tank-side metalworking fluids

Recommended levels/use: The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level of 100 ppm, added as needed tank-side, is recommended.

Storage/handling: Always mix prior to use as the product tends to separate slightly. Mix product and retest for quality after one year from the date of manufacture. The minimum shelf life in closed containers is 12 months from the date of manufacture. Refer to Material Safety Data Sheet for additional handling information.

Packaging: Drums holding 390 lbs/ 177 kg net or 5 gallon pail holding 35 lbs/ 16 kg net.