

# FOAM BAN<sup>®</sup> TS-7250

## TECHNICAL INFORMATION

### Defoamer for aqueous systems

**Composition:** Blend of 3-Dimensional Siloxane and polyoxyalkylene technology

**Appearance:** liquid  
**Colour:** off-white

**Typical Properties:**

Active ingredients:	approx. 99%
Consistency/Viscosity:	approx. 600 mPas /cps
Density at 20°C:	approx. 8.44 lbs/gal
Emulsifiable:	Moderate
pH (2% in dist. water):	approx.

*This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product. For specifications please consult the Certificate of Analysis.*

**Properties/applications:** A high efficiency, 3-Dimensional Siloxane compound defoamer specifically designed to rupture and dissipate tank-side foam in the metalworking industry. The defoamer provides both initial foam knockdown, as well as long-term defoaming persistence.

Main applications:  
- Metalworking Tank Side

**Recommended levels/use:** The properties and performance of a defoamer are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance prior to use. A starting dosage level of 100 ppm or as needed based on the volume of the system.

**Storage/handling:** Always mix prior to use as the product tends to separate slightly  
Mix product and retest for quality after one year from the date of manufacture.  
The minimum shelf life in closed containers is 12 months from the date of manufacture.  
Refer to Material Safety Data Sheet for additional handling information.

**Packaging:** Drums holding 470 lbs/ 213 kg net or 5 gallon pail holding 42 lbs/ 19 kg net.

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.

EN

Revision 05/14: